


ClaronPolyseal®
Double Acting Piston Seal
Metric
SPW



Nominal Dimensions & Machining Tolerances

Claron Part Number	H9	+0.00	+0.20	Nominal
	ØD_1	-0.20 Ød_1	-0.00 L_1	
SPW 050	50	36	9.0	4.0
SPW 060	60	46	9.0	4.0
SPW 065	65	50	11.0	5.0
SPW 070	70	55	11.0	5.0
SPW 075	75	60	11.0	5.0
SPW 080	80	65	11.0	5.0
SPW 085	85	70	11.0	5.0
SPW 090	90	75	11.0	5.0
SPW 095	95	80	11.0	5.0
SPW 100	100	85	12.5	5.0
SPW 105	105	90	12.5	5.0
SPW 108	108	93	12.5	5.0
SPW 110	110	95	12.5	5.0
SPW 115	115	100	12.5	6.5
SPW 120	120	105	12.5	6.5
SPW 125	125	102	16.0	6.5
SPW 130	130	107	16.0	6.5
SPW 135	135	112	16.0	6.5
SPW 140	140	117	16.0	6.5
SPW 145	145	122	16.0	6.5
SPW 150	150	127	16.0	6.5
SPW 160	160	137	16.0	6.5
SPW 165	165	142	16.0	6.5
SPW 170	170	147	16.0	6.5
SPW 180	180	157	16.0	6.5
SPW 185	185	162	16.0	6.5
SPW 190	190	167	16.0	6.5
SPW 200	200	177	16.0	6.5
SPW 210	210	187	16.0	6.5
SPW 225	225	202	16.0	6.5
SPW 250	250	222	17.5	7.5