



ClaronPolyseal®
Single Acting Piston Seal

GP

Metric





Nominal Dimensions & Machining Tolerances

Claron Part Number	H 10	js11	+0.25 -0.00	Nominal	Min	Max
	$\varnothing D_1$	$\varnothing d_1$	L_1	Sec. S	Chamf. C	R_1
GP157118	40	30	7.0	5.0	2.5	0.4
GP196157	50	40	7.0	5.0	2.5	0.4
GP236196	60	50	7.0	5.0	2.5	0.4
GP279220	71	56	10.0	7.5	4.0	0.8
GP275236	70	60	7.0	5.0	2.5	0.4
GP314236	80	60	13.0	10.0	5.0	0.8
GP307248	78	63	10.0	7.5	4.0	0.8
GP334275	85	70	12.5	7.5	4.0	0.8
GP354275	90	70	13.0	10.0	5.0	0.8
GP393314	100	80	13.0	10.0	5.0	0.8
GP433354	110	90	13.0	10.0	5.0	0.8

ClaronPolyseal®
Single Acting Piston Seal

GP

Imperial



Nominal Dimensions & Machining Tolerances

Claron Part Number	H 10	js11	+0.025 +0.015 L ₁	Nominal Sec. S	Min Chamf. C	Max R ₁
	ØD ₁	Ød ₁				
GP 150100	1.500	1.000	0.375	0.250	0.125	0.015
GP 200150	2.000	1.500	0.375	0.250	0.125	0.015
GP 200150/1	2.000	1.500	0.468	0.250	0.125	0.015
GP 212150	2.125	1.500	0.468	0.313	0.156	0.015
GP 237200/1	2.375	2.000	0.360	0.188	0.093	0.010
GP 262200/1	2.625	2.000	0.312	0.313	0.156	0.015
GP 300237	3.000	2.375	0.312	0.313	0.156	0.015
GP 325250/1	3.250	2.500	0.562	0.375	0.187	0.032