



ClaronPolyseal®
Single Acting Rod Seal
PDS Metric



Nominal Dimensions & Machining Tolerances

Claron Part Number	f8	H9	Js11	+0.25 -0.00 L ₁	Nominal Section S	Min. C	Max. R ₁
	Ød ₁	ØG	ØD ₁				
PDS 169118	30		43	20.0	6.5	3	0.4
PDS 204157	40		52	22.5	6.0	3	0.4
PDS 216157	40		55	22.5	7.5	4	0.4
PDS 248196	50		63	20.0	6.5	3	0.4
PDS 255196	50		65	22.5	7.5	4	0.4
PDS 295236	60		75	22.5	7.5	4	0.4



Nominal Dimensions & Machining Tolerances

Claron Part Number	f8	H9	Js11	+0.010 -0.000 L ₁	Nominal	Min.	Max.
	Ød ₁	ØG	ØD ₁		S	C	R ₁
PDS 175125	1.250		1.750	0.750	0.250	0.125	0.015
PDS 200150	1.500		2.000	0.748	0.250	0.125	0.015
PDS 237175	1.750		2.375	1.060	0.312	0.156	0.015
PDS 250200	2.000		2.500	0.850	0.250	0.125	0.015
PDS 262200	2.000		2.625	1.000	0.312	0.156	0.015
PDS 325250	2.500		3.250	1.230	0.375	0.187	0.032