



ClaronPolyseal®  
Single Acting Rod Wiper Seal



Metric

# CSWM



## Nominal Dimensions & Machining Tolerances

Claron Part Number	Refer Seal Selection $\varnothing d_1$	+0.20 -0.00 $\varnothing D_1$	+0.20 -0.00 $\varnothing D_2$	+0.20 -0.00 $L_1$	Nominal $L_2$
CSWM 016	16	26	24.5	4.5	6.5
CSWM 018	18	28	26.5	4.5	6.5
CSWM 020	20	33	31.5	6.0	8.5
CSWM 022	22	35	33.5	6.0	8.5
CSWM 025	25	38	36.5	6.0	8.5
CSWM 028	28	41	39.5	6.0	8.5
CSWM 030	30	43	41.5	6.0	8.5
CSWM 032	32	45	43.5	6.0	8.5
CSWM 036	36	49	47.5	6.0	8.5
CSWM 040	40	53	51.5	6.0	8.5
CSWM 045	45	58	56.5	6.0	8.5
CSWM 050	50	63	61.5	6.0	8.5
CSWM 055	55	68	66.5	6.0	8.5
CSWM 056	56	69	67.5	6.0	8.5
CSWM 060	60	73	71.5	6.0	8.5
CSWM 063	63	76	74.5	6.0	8.5
CWSM 065	65	78	76.5	6.0	8.5
CSWM 070	70	83	81.5	6.0	8.5
CSWM 080	80	93	91.5	6.0	8.5
CSWM 090	90	103	101.5	6.0	8.5
CSWM 100	100	113	111.5	6.0	8.5



## Nominal Dimensions &amp; Machining Tolerances

Claron Part Number	Refer Seal Selection $\text{Ød}_1$	+0.008 -0.000 $\text{ØD}_1$	+0.008 -0.000 $\text{ØD}_2$	+0.008 -0.000 $L_1$	Nominal $L_2$
CSW 050	0.500	0.875	0.812	0.172	0.250
CSW 062	0.625	1.000	0.938	0.172	0.250
CSW 075	0.750	1.250	1.187	0.234	0.345
CSW 087	0.875	1.375	1.312	0.234	0.345
CSW 100	1.000	1.500	1.437	0.234	0.345
CSW 112	1.125	1.625	1.562	0.234	0.345
CSW 125	1.250	1.750	1.687	0.234	0.345
CSW 137	1.375	1.875	1.812	0.234	0.345
CSW 150	1.500	2.000	1.937	0.234	0.345
CSW 162	1.625	2.125	2.062	0.234	0.345
CSW 175	1.750	2.250	2.187	0.234	0.345
CSW 200	2.000	2.500	2.437	0.234	0.345
CSW 212	2.125	2.625	2.562	0.234	0.345
CSW 225	2.250	2.750	2.687	0.234	0.345
CSW 250	2.500	3.000	2.937	0.234	0.345
CSW 275	2.750	3.250	3.187	0.234	0.345
CSW 300	3.000	3.500	3.437	0.234	0.345
CSW 325	3.250	3.750	3.687	0.234	0.345
CSW 350	3.500	4.000	3.937	0.234	0.345
CSW 375	3.750	4.250	4.187	0.234	0.345
CSW 400	4.000	4.500	4.437	0.234	0.345