

ClaronPolyseal®
Double Acting Rod Wiper Seal

Metric

PWD

Nominal Dimensions & Machining Tolerances

Claron Part Number	Refer Seal Selection $\text{Ø}d_1$	H11 $\text{Ø}D_1$	H11 $\text{Ø}D_2$	+0.10 -0.00 L_1	Min. L_2
PWD 025/1	25	33.6	28	5.3	7
PWD 030	30	38.0	33	5.2	6
PWD 030/2	30	40.0	35	7.0	10
PWD 035/1	35	43.6	38	5.3	7
PWD 040	40	48.0	43	5.2	6
PWD 042/1	42	50.6	45	5.3	7
PWD 045/2	45	55.6	48	5.3	7
PWD 048/1	48	56.6	51	5.3	7
PWD 050	50	58.0	53	5.2	6
PWD 055/2	55	65.6	58	5.3	7
PWD 060	60	70.0	63	6.2	7
PWD 065	65	75.0	68	6.2	7
PWD 070	70	80.0	73	6.2	7
PWD 075	75	85.0	78	6.2	7
PWD 080	80	90.0	83	6.2	7
PWD 085	85	95.0	88	6.2	7
PWD 090	90	100.0	93	6.2	7
PWD 095	95	105.0	98	6.2	7
PWD 100	100	110.0	103	6.2	7